

RF-CS



RF-Contact with Sensor

Numerous years of experience with Inertia Sensors have been combined with our advanced wireless platform to create an outstanding RF-Shock (inertia)/Contact detector.

It comes with magnetic contacts as standard - a non-sensor head option is also available. It has superb RF range in a compact housing.

- Two-way wireless communication
- Contains battery
- Magnetic contact
- Additional alarm & tamper terminals
- Available in white & brown
- Resin protected electronics
- Battery: CR123A 3V Lithium
- Quiescent Current: 7 μ A
- Transmit Current: 40mA
- Temperature: -10 to +40 $^{\circ}$ C
- Weight (inc. magnet & sensor): 100g
- Size: 122mm x 33mm x 33mm (main unit)
- Size: 78mm x 18mm x 12mm (magnet)
- EN 50131-2-6 Grade 2 Class II
- EN Grade 2
- Environmental Class II



RF-CSW (Contact Sensor - White)

RF-CSB (Contact Sensor - Brown)

SecureWave
868MHz Radio

www.hkcsecurity.com

Thank you for considering HKC products for your security system.

For further information in relation to any of our products, please contact us at:

HKC Ltd.
Parkway Business Centre, Ballymount,
Dublin 24, Ireland.
T: 353 1 456 7007
F: 353 1 456 8332
E: sales@hkc.ie

HKC Ltd.
James Hill Street,
Littleborough,
Lancashire.
OL12 0HA
T: 44 1706 373560
F: 44 1706 378460

or visit us at www.hkcsecurity.com

UK Technical Support: 01706 838746 or 0800 111 4599

Safe & Secure